



SuperFlex Flexible Shaft Wood Drills

Bordo's range of SuperFlex drills are ideal for installing wire or cable inside existing timber stud walls. The flexible spring steel shaft allows maximum flexibility of drilling position within the wall cavity. The extreme reach of SuperFlex drills (up to 1.8m) simplifies the previously time consuming task of drilling through noggins, top plates, bottom plates or studs inside finished walls.

The SuperFlex drill features a double fluted reduced taper auger head with a self feeding lead screw point, fishing eyes at both ends, flexible memory retention shaft with flattened ends to ensure a positive chuck engagement.

SuperFlex Wood Bit Range

| Diameter inch | OAL m / inch | Part Number |
|------------------|-----------------|----------------|
| 3/8 | 1.372 / 54 | 2680-3/8x54 |
| 1/2 | 1.372 / 54 | 2680-1/2x54 |
| 9/16 | 1.372 / 54 | 2680-9/16x54 |
| 3/4 | 1.372 / 54 | 2680-3/4x54 |
| 3/8 | 1.829 / 72 | 2680-3/8x72 |
| 1/2 | 1.829 / 72 | 2680-1/2x72 |
| 9/16 | 1.829 / 72 | 2680-9/16x72 |
| 3/4 | 1.829 / 72 | 2680-3/4x72 |

Positioning Handle 2680-PH



SuperFlex positioning handle for accurate drill positioning



Aggressive lead screw point for fast starting



Use fishing eyes to attach cables/wires for easy pull through



Drill horizontally through studs



Drill vertically through noggins and plates



Flexible spring steel shaft with high memory retention. Available in 54" or 72" overall lengths.

Shorter lengths are available on request.

Contact Bordo International for further information

ABN 96 005 125 833

3 Kingston Park Court, PO Box 9199, Scoresby, Victoria 3179 Australia

T +61 3 9212 7000 F +61 3 9212 7070 E info@bordo.com.au W www.bordo.com.au

drills superflex

single

high carbon & spring steel



| group | FLEX | |
|----------------------------------|----------------------------------|--|
| surface finish | black | |
| material | high carbon and spring steel | |
| point type | self feeding screw | |
| flute type | double flute reduced taper auger | |
| fishing eyes / bell hanger holes | both ends | |
| packaging | hang sell | |

SUPERFLEX DRILLS

Bordo's range of SuperFlex drills are ideal for installing wire or cable inside existing timber stud walls. The flexible spring steel shaft allows maximum flexibility of drilling position within the wall cavity. The extreme reach of SuperFlex drills (up to 1.8m) simplifies the previously time consuming task of drilling through noggins, top plates, bottom plates or studs inside finished walls.

The SuperFlex drill features a double fluted reduced taper auger head with a self feeding lead screw point, fishing eyes at both ends, flexible memory retention shaft with flattened ends to ensure a positive chuck engagement.

| DIA inch | OAL mm | OAL inch | SHANK inch | PACK qty | \$ each | Part number |
|-------------|-----------|-------------|---------------|-------------|------------|----------------|
| 3/8 | 1370 | 54 | 3/16 | 1 | 115.18 | 2680-3/8x54 |
| 1/2 | 1370 | 54 | 3/16 | 1 | 117.66 | 2680-1/2x54 |
| 9/16 | 1370 | 54 | 3/16 | 1 | 128.11 | 2680-9/16x54 |
| 3/4 | 1370 | 54 | 1/4 | 1 | 172.72 | 2680-3/4x54 |
| 3/8 | 1830 | 72 | 3/16 | 1 | 124.89 | 2680-3/8x72 |
| 1/2 | 1830 | 72 | 3/16 | 1 | 127.38 | 2680-1/2x72 |
| 9/16 | 1830 | 72 | 9/16 | 1 | 137.82 | 2680-9/16x72 |
| 3/4 | 1830 | 72 | 1/4 | 1 | 186.58 | 2680-3/4x72 |

Shorter lengths are available on request



| ACCESSORIES | \$ each | Part number |
|------------------------------------|------------|----------------|
| Superflex drill positioning handle | 72.58 | 2680-PH |



SuperFlex positioning handle for accurate positioning



Aggressive lead screw point for fast starting



Use fishing eyes for easy cable pull through



Drill vertically through noggins and plates



Drill through studs