



Insert Part Number		3732-6GMTW
Military Specification		MS51830-103
Reference Number		KNC0632J
Insert Type		Miniature
Internal Thread Form		UNJC
Internal Thread Size		6-32
External Thread Size		12-28
External Thread Length	inch	0.125
Nominal Length Q	inch	0.170
Insert Material		Stainless Steel - 303 CRES
Insert Finish		Passivated
Insert Coating		-

Loksert solid keylocking inserts are an easily installed thread assembly that are ideal for replacing damaged or worn threads in virtually any material - ferrous, non-ferrous and non-metallic. They are constructed from high quality carbon steel or extremely hard wearing stainless steel. One piece Loksert inserts are supplied with the dove-tailed locking keys pre-assembled. The pre-positioned keys automatically position the insert at the correct depth below the surface of the parent material. Lokserts are suitable for repairing and creating threads in a wide range of applications including forgings and castings and are especially suited to situations that experience heavy wear and vibration - such as mining, construction and earthmoving equipment.

COMPATIBLE LOKSERT INSTALLATION AND REMOVAL TOOLS	
TOOL TYPE	Part #
Hand Installation tool - Miniature	3732-6GMTWT
Hand Installation tool - Thin Wall	-
Hand Installation tool - Heavy Duty	-
Hand Installation tool - Universal (TW & HD)	-
Hand Installation tool - Extra Heavy Duty	-
Hand Installation tool - Solid	-
Pneumatic Front End Assembly (FEA)	-
Pneumatic Tool	-

powercoil.com.au

PowerCoil and Loksert are registered trademarks of Bordo International Pty Ltd Australia



DRILLED HOLE DIMENSIONS INTERMEDIATE/PLUG TAP

A Tapping Drill Size	mm	4.75
A Tapping Drill Size	inch	0.187
Tapping Drill Part Number		



TAPPED HOLE DIMENSIONS

Tap Size		12-28
Tap Tolerance		2B
T Tapping Depth minimum	mm	-
T Tapping Depth minimum	inch	0.160
Loksert Tap Part Number	Intermediate	3734-12GI
C Countersink Width minimum	mm	-
C Countersink Width minimum	inch	0.220



INSERT SPECIFICATIONS

Internal Thread		6-32
Internal Thread Tolerance		UNCJ-3B
External Thread		12-28
External Thread Tolerance		UNF-2A
Q Nominal Length	inch	0.170
Locking Keys	#	2



INSERT REMOVAL SPECIFICATIONS

R1 Drill Size	mm	-
R1 Drill Size	inch	#21
R2 Drill Depth minimum	mm	-
R2 Drill Depth minimum	inch	3/32



IMPORTANT The success of any drilling and tapping operation is dependant upon many factors -type of material being cut, cutting speed, coolant, equipment being used - and it is not possible to give specific drill sizes for each material. Drill sizes shown are recommendations only and Bordo International would strongly suggest that independent testing be performed for specific and critical applications.

For detailed removal instructions please visit powercoil.com.au